



Research Article

Exploring Passive Heat Transfer Enhancement Techniques: Applications, Benefits, and Challenges

F. Mebarek-Oudina^{1,*}, ¹ *Department of Physics, Faculty of Sciences, University of 20 Août 1955-Skikda, Skikda, Algeria***ARTICLE INFO**

Article History

Received 15 Sep 2024

Revised: 16 Oct 2024

Accepted 15 Nov 2024

Published 05 Dec 2024

Keywords

Passive heat transfer

Thermal management

Surface roughness

Extended surfaces

**ABSTRACT**

Techniques for enhancing passive heat transfer play a crucial role in boosting thermal performance in engineering systems without the need for external energy sources. These approaches, such as altering surface roughness, utilizing extended surfaces, incorporating porous media, and employing phase change materials, provide energy-efficient and economical solutions for a variety of uses, including automotive systems, HVAC, and cooling in electronics. This paper examines important passive techniques, focusing on their fundamental principles, real-world applications, and the challenges that come with them. The study highlights the importance of sustainability and energy efficiency, showcasing how these approaches can meet contemporary thermal management challenges, even while facing issues such as material degradation and pressure drops in systems.

1. INTRODUCTION

Effective heat transfer is fundamental to several technical and industrial applications, including energy systems, electronics cooling, and thermal management in the aerospace and automotive sectors. Conventional approaches frequently depend on active procedures that utilize external energy sources, such as pumps or fans, to improve heat transmission. Nonetheless, these methods may bring complexity, elevate operating expenses, and diminish overall system efficiency. Passive heat transfer augmentation methods provide an effective option by augmenting thermal performance without requiring external energy sources [1-3]. These technologies employ design improvements, material characteristics, and fluid dynamics to enhance natural heat transmission. Passive approaches provide a variety of solutions adapted to individual applications, including surface changes such as fins and dimples, as well as the implementation of extended surfaces and swirl flow devices [4-6].

This paper examines several passive heat transfer augmentation approaches, highlighting their uses, advantages, and associated issues. This study seeks to establish a basis for further research and innovation in the creation of energy-efficient and economically viable thermal management technologies by integrating knowledge in this domain.

2. OVERVIEW OF PASSIVE HEAT TRANSFER ENHANCEMENT

Passive heat transfer enhancement methods are techniques that improve heat transfer behavior without the need for external energy sources. Instead, these methods make use of inherent physical properties and arrangements that occur naturally or are induced in a system [6-8]. Passive heat transfer methods improve conductivity, and convective heat transfer based on basic scientific principles such as fluid mixing, surface area increase, and phase change [9]. Passive heat transfer enhancement techniques such as surface roughness, extended surfaces, and porous media are based on these fundamental principles. Passive heat transfer enhancement methods are important in applications where energy usage must be minimized, such as in energy-efficient buildings, industrial processes, and heat exchanger designs. With the increasing global concern about energy use and sustainability, passive heat transfer enhancement methods have only solidified their importance in minimizing energy usage in designs and applications while continuing to meet performance and output specifications [10]. Passive heat transfer enhancement methods can help save cost and conserve energy in industrial applications. Passive methods are utilized in those processes where no external energy can be spent to utilize such methods.

*Corresponding author. f.mebarek_oudina@univ-skikda.dz

Such methods take advantage of the physical properties of substances for the purpose enhancement of heat transfer processes. For example, extended surface can be applied which is usually implemented to enhance heat transfer from the heat carrier into surrounding to preserve desired conditions in the equipment while the costs on energy are reduced [11]. Rough surfaces and porous media are also utilized for passive heat transfer enhancement which disrupts boundary flow on the heat exchange surface [12]. It can be also applied in processes where this energy is not supposed to be spent. Utilization of passive heat transfer enhancement techniques in industrial applications can save considerable amounts of energy and cut costs. This is of a major importance for implementation of sustainability policies on global and corporate level, being regarded as a competitive advantage.

3. TECHNIQUES FOR PASSIVE HEAT TRANSFER ENHANCEMENT

In passive systems, several methods are available to augment heat transfer. Each of these methods uses a distinct typology to ameliorate heat transfer. Among the most popular methods is the use of extended surfaces i.e. fins. Fins are an efficient mechanism to transfer heat from the surface to the surrounding medium by augmenting the surface area of the material [11]. Another method to enhance heat transfer characteristics is by augmenting surface roughness. Surface roughness disrupts boundary layers and improved fluid mismatching characteristics and convective heat transfer [12]. The use of porous material takes advantage of its own respective structure. The material augment heat conduction due to the permeation nature of the fluid, and the morphology enhances conductivity [10]. The use of phase change material (PCM) is different from the aforementioned methods. The use of PCM ameliorate heat stability due its latent property of absorbing and releasing heat during phase change which stabilizing temperature fluctuations and evolve time for heat storage [13]. While passive heat transfer methods offer significant advantages, the integration of these techniques with active systems could further enhance overall efficiency. Combining passive methods with smart materials and control systems might optimize the heat transfer process, adapting to varying environmental conditions and operational demands. This hybrid approach could lead to more resilient and adaptable systems, especially important in industries facing fluctuating thermal loads. Additionally, exploring the potential of biomimicry in designing passive heat transfer systems could unlock innovative solutions inspired by natural processes, offering sustainable and efficient pathways for energy management.

3.1 Extended Surfaces (Fins)

Fins or extended surfaces are one of the most common types of structures that enhance the heat transfer performance. These are the surfaces, which are projected from a base surface and allow for more heat transfer with the surrounding medium [11]. The main benefit of using fins is that they enhance the heat transfer performance without the need for any power input. Hence, they are suitable for a passive enhancement of the heat transfer. Fins are used extensively in many applications. For example, in radiators they are used to enhance the heat dissipation from the engines. They are also used in most of the heat exchangers to maintain the optimal operating temperatures in industries. Fins are versatile structures, and can be designed in many ways depending on the requirements. Their importance revealed in various applications ensures that they are used as a common tool for energy efficiency [14]. Heat transfer efficiency, the effectiveness of fins will depend on the environmental conditions and materials used for constructing the fins. Also, the fins constructed of high conductive materials like aluminum or copper also aid in transferring heat quickly as they have high thermal conductivity [14]. Also, in high-temperature applications, the fins' material should withstand oxidation and thermal material degradation, defeating the purpose of transferring heat over time. Further, environmental conditions like airflow and humidity will affect the rate of convective heat transfer, impacting the fins' efficiency [11]. Finally, the fins' design and arrangement can be further optimized to maximize heat dissipation in low airflow settings or where the thermal loads vary considerably.

3.2 Surfaces roughness

Surface Roughness is a passive method and have a tremendous effect on the heat transfer enhancement by disturbing the boundary layer next to the surface and making it more turbulent, hence increasing the convective heat transfer coefficient due to these disturbances leading to more turbulent and mixing in the fluid [12]. The performance of rough surface for heat transfer application is associated with the flow disturbances they caused compared to the smooth surfaces that have lower heat transfer coefficient. This method is primarily used in the design of heat exchangers and other electronic devices cooling where heat transfer and heat dissipation are critical and dominant factor in the device performance and operation. The clever use of surface roughness can also help save a significant amount of power/energy by improving the heat transfer performance and characteristics in heat transfer devices and systems and promote energy and efficient use in different applications and processes. The application of surface roughness for heat transfer is widespread and is adopted in different industries. In the aerospace industry, turbine blades and heat exchangers are adapted with rough surfaces to improve heat transfer performance at high temperatures and velocities, thus improving thermal reliability and efficiency [12]. The

chemical processing industry uses surface roughness in reactors and heat exchangers to promote turbulent flows at operational levels, ensuring that the reaction kinetics is maintained with the processed heat applied. In the electronics, surface roughness is applied in cooling systems of high-performance computing systems to enhance the heat transfer rates to prevent overheating and performance lags [12]. In the automotive industry, surface roughness is employed in engine cooling systems to improve heat exchange, which also affects the overall fuel economy. This is also useful to meet the world's standards on emissions and efficiency of vehicles for a cleaner environment.

3.3 Porous Media

Passive heat transfer enhancement with porous structures is based on the innate characteristics of the material. Metal foams or sintered metals are examples of the porous materials which exhibit enhanced heat transfer due to fluid dispersion and increased thermal conductivity through their interconnected porosity [10]. Enhanced heat transfer through a porous structure is primarily due to a higher surface contact area of the heat transfer fluid with the solid matrix, which disturbs the thermal boundary layer and promotes convective heat transfer. Porous structures with passive heat transfer enhancement techniques are commonly observed in devices to maintain a uniform temperature profile, e.g. heat exchangers and thermal management systems. The use of porous structures can enhance heat dissipation leading to increased energy efficient practices, decreasing the reliance on active cooling methods, and contributing to sustainability targets [9]. The characteristics of porous media improve thermal conductivity. Its high surface area and enhanced fluid mixing are beneficial in passive heat transfer applications. Such materials are applicable to systems that seek uniform temperature propagation, such as heat exchangers and electronics thermal management. One disadvantage of using porous material is the possible pressure drop and material wear, which can lead to the reduced efficacy of system operations over time [10]. Importantly, the type of porous material used must also be appropriate to the application environment. Thermal performance must be considered in relation to possible operational downsides, wherein the use of porous media should be justified for its benefits.

3.4 Phase Change Material (PCM)

PCMs (phase change materials) act as passive heat transfer enhancers by absorbing and releasing latent heat when changing their state. This capability of PCMs to maintain temperature stability allows their application in thermal energy storage [15], the use of which optimizes heat transfer and even lowers energy consumption by reducing the demand for active cooling systems. PCMs are also successfully embedded in building materials to increase energy efficiency by maintaining comfortable temperature levels of indoor spaces, which is one of the main requirements for modern energy-efficient constructions [13]. Effective regulation of thermal loads helps to decrease energy consumption, thus energy-efficient technologies become widely used in different product areas, including construction and electronics. The real-life application of phase change material (PCM) revolves around managing heat loads using latent heat. They are mostly used as an additive to construction materials and electronic devices. In construction materials, PCMs moderate indoor temperature and thereby limit heating and cooling needs [13]. They also reduce the energy load through the building's lifetime; therefore, are considered sustainable materials. In electronics construction, they are used to manage overheating in devices to prolong the lifespan of electronic components [15]. PCMs have been used in thermal management of solar energy systems. Stability in temperature fluctuations improves performance and efficiency of solar panels and solar unit [15].

3.5 Additives

The use of an additive to produce a fluid with enhanced thermal properties so that it can easily conduct heat is an additional method of improving a fluid's thermal conductivity. Nanoparticles are commonly used as an additive and suspended in the base fluid to increase the thermal conductivity of the fluid while also changing other physical properties of the fluid such as its specific heat, viscosity, etc. [9]. The use of nanoparticles improves the heat transfer rates of fluids and the stability of thermal systems making it more efficient. In vehicles, the use of nanofluids in cooling systems to maintain engine performance increases heat management thereby increasing efficiency and fuel use [11]. The addition of additives to improve fluid heat transfer gives promising results as it consumes less energy and ensures proper heat management therefore making it an attractive choice for sustainable and efficient heat transfer applications.

4. APPLICATIONS OF PASSIVE HEAT TRANSFER ENHANCEMENT

The passive methods are used in different sectors for their advantages. In construction, the phase change materials (PCMs) are used to keep the building temperatures under control, minimizing the active air conditioning and heating needs [13]. In the automotive sector, the extended surfaces (fins) are utilized in radiators and cooling systems, contributing to fuel savings and efficiency [11]. The surface roughness is useful in the electronics industry to improve cooling of the high-tech devices for more efficient heat extraction and avoid overheating [12]. Overall, these applications show the usefulness of the passive heat transfer enhancement and their implementation in the modern technology.

4.1 Automotive Industry

Passive heat transfer techniques are widely used in the automotive industry for cooling system designs essential for effective engine heat management for desired performance and efficiency. In radiators, extended surfaces (fins) are also employed for heat dissipation to maintain temperature of engine design components [11]. Surface roughness is used to improve heat transfer in the engine cooling design systems, where turbulent flow increases the convective heat transfer coefficient for desired heat management over varying engine loads [12]. In nanofluids, nanoparticles are used in the cooling liquid design that enhances thermal conductivity and suspension stability to improve the heat transfer rate to improve engine efficiency [9]. These passive heat transfer design techniques also serve the automotive industry in achieving energy efficiency goals for sustainability and supporting innovation for more eco-friendly solutions. Passive heat transfer methods are a means to greatly optimize the usage of automotive systems in operation. The performance and fuel efficiency of vehicles are greatly improved through the automotive applications involving extreme heat transfer and optimal engine efficiency. Extensions surface-based vehicles encompassing fins, are best suited for transmitting heat when dealing with surface area input to motor systems. It is crucial to keep the engine temperature within working operational ranges to be optimal for electronic performance [11]. Heat transfer capabilities of automotive engine cooling systems are further improved through the use of surface roughness. This passive heating element increases fluidics stability and fuels efficiency in the range of varying engine operating temperatures [12]. Further optimization method implementation examines the use of nanofluids that encompass nanoparticles within automotive engine cooling devices. By using this passive heat transfer element, automotive systems recorded further increases in heat transfer and fluidics and automotive refinement including propulsion and stability [9]. All heat transfer methods for automotive applications contribute towards automotive system optimization while efficiently consuming energy on the road. Automotive energy loss optimization reflects vehicles industry's innovative future plans for energy efficiency and reduction.

4.2 HVAC Systems

Passive heat transfer techniques are critical to HVAC systems solution to deliver better energy savings and reducing their operating costs in residential and commercial buildings. phase change materials (PCMs), surface roughness, are effective methods to passive heat transfer techniques in HVAC systems [13]. PCMs have capability to absorb and release latent heat, active heat transfer is reduced and maintain the building temperature stability to HVAC systems[13]. Surface roughness of HVAC systems components such as heat exchangers, increase heat transfer through convection and pressure drops, turbulence improvements, and increases the system efficiency [12]. These passive heating techniques not only lead to high energy savings from HVAC systems but can hierarchize the sustainable building performance, and matching the global targets of reducing energy consumptions, and reducing carbon footprint of buildings. There are several case studies that show the passive heat transfer techniques can be implied in commercial and residential buildings and how they improve overall energy efficiency. One of them is the implementation of phase change materials (PMS) in building enclosures to minimize energy use for heating and cooling. The study shows that PMS can trap the excess heat during warmer days and release them at night, thus keeping the inner temperature steady and reducing the reliance on active heating and cooling systems [13]. Another case study showed the application of surface roughness in heat exchangers used in HVAC systems to improve the convective heat transfer coefficients and efficiency [12]. These case studies demonstrate how passive heat transfer techniques can be incorporated in building designs and constructions, aiding in energy conservation practices while minimizing operating costs without compromising the comfort of the occupants.

4.3 Electronics Cooling

In the case of electronic cooling, the miniaturization trend has presented several difficulties that can be mitigated through the use of passive techniques. In a miniaturized electronic system, it is difficult to achieve optimal heat transfer from the devices due to their reduced size and the absence of other energy inputs to maximize heat diffusion. Surface roughness is one of the passive techniques that can be employed to facilitate heat transfer in an electronic component, as it increases the turbulence in the flow and reduces the effect of the boundary layer that may develop in the component [12]. The operation of phase change materials (PCMs) in electronic components relies on the principle of latent heat, which helps to keep the temperature of the device constant during the melting process and to maintain it at a certain level during solidification [15]. In the context of electronics, the ability of PCMs to mitigate overheating conditions becomes critical in the miniaturization component increasing demand in the electronics industry. Through the improvements provided by passive techniques, life expectancy and reliability of components used in the miniaturized electronic design are also increased. Further, applicability of passive heat transfer methods is also significant to prolong the life and reliability of electronic components. Surface roughness and phase change material (PCM) assist in better cooling of the electronic devices and these methods detach thermal stress from the electronic devices. Surface roughness improves heating transfer because it creates disturbance in boundary layers [12]. Surface roughness helps electronic components to operate within a specific temperature limit. Further overheating threats are eliminated through surface roughness. PCM absorbs latent heat when temperature increases and

releases heat when temperature decreases. This method is also effective to eliminate temperature cycles. Electronics components are also affected by thermal cycling and these passive methods help to eliminate collapse of the electronic components [15]. Electronics industry needs enhancement in components operational efficiency and reliability. The passive methods discussed in this sub-section are also assisting electronics in improvement of life cycle of components as components are used in digital devices and these devices are minimising in size.

4.4 Benefits and Challenges

The advantages of passive heat transfer techniques are prominent because they contribute a lot to improving sustainability and cost-effectiveness. Putting the physical characteristics to good use means that there is little need to invest energy externally and it also helps in addressing the challenges brought about by energy demands worldwide and carbon emissions[9]. For example, the utilization of integrating phase change material in structural design greatly impacts energy efficiency because it maintains a certain temperature indoors, hence, less dependence on active heating and cooling systems in buildings[13]. Similarly, using surface roughness and nanofluids as passive techniques in the industry ensures more optimal thermal management to the system resulting in better operational costs and performance[12]. Nevertheless, there are implications that can arise with the adoption of passive methods such as material degradation and associated pressure drops; hence, did they still require corresponding solutions that will ensure longevity of effects and confirm that they suit the particular application conditions[10]. There are several challenges and limitations. Material degradation can affect heat transfer efficiency over time for passive methods like surface roughness and porous media [10]. Moreover, incorporating surface roughness can result in increased pressure drops, adversely affecting heat transfer performance as well as fluid dynamics [12]. While employing phase change materials enhances thermal storage, limitations due to thermal cycling and phase separation can pose a challenge [15]. Hence, material selection and configuration design are dependent on specific environmental and operational conditions.

5.CONCLUSION

In summary, the passive techniques for heat transfer enhancement are important contributors on the way to improving energy efficiency in all fields. Extensions surfaces, surface roughness, use of porous media, and phase change materials techniques are few of the best-known approaches which lead to thermal enhancement in passive mode. These techniques can be applied on several industries, such as automotive, air-conditioning, electronic devices humidification and dehumidification and building design to improve the thermal efficiency, equipment performance and reduce the operational costs. Also, although there are challenges associated with the passive technique, including material degradation and pressure drops along the system, the importance, and contribution of these techniques towards sustainability, and fighting energy wastage is significant. The importance of passive methods has been clarified as we are heading to achieve sustainability environmental objectives, such as energy consumption reduction, and therefore there is high potential for the future applications of passive heat transfer

Conflicts Of Interest

The author's paper explicitly states that there are no conflicts of interest to be disclosed.

Funding

The author's paper clearly indicates that the research was conducted without any funding from external sources.

Acknowledgment

The author acknowledges the institution for their commitment to fostering a research-oriented culture and providing a platform for knowledge dissemination.

References

- [1] M. J. Al-Dulaimi, F. A. Kareem, and F. A. Hamad, "Numerical investigation of the heat transfer enhancement inside a square duct with rectangular vortex generators," *Journal of Thermal Engineering*, vol. 8, no. 1, pp. 1–13, Feb. 2022, doi: 10.18186/thermal.1066981.
- [2] K. A. Ameen, H. A. Hasan, M. J. Al-Dulaimi, A. M. Abed, and H. F. Al-Qrimli, "Improving the performance of air conditioning unit by using a hybrid technique," *MethodsX*, vol. 9, p. 101620, 2022, doi: 10.1016/j.mex.2022.101620.
- [3] M. J. Al-Dulaimi, F. A. Kareem, and F. A. Hamad, "Numerical investigation of the heat transfer enhancement inside a square duct with rectangular vortex generators," *Journal of Thermal Engineering*, vol. 8, no. 1, pp. 1–13, Feb. 2022, doi: 10.18186/thermal.1066981.

- [4] A. Mezaache, F. Mebarek-Oudina, H. Vaidya, and Y. Fouad, "Heat transfer analysis of nanofluid flow with entropy generation in a corrugated heat exchanger channel partially filled with porous medium," *Heat Transfer*, vol. 53, no. 8, pp. 4625–4647, Aug. 2024, doi: 10.1002/htj.23149.
- [5] G. Dharmiah, F. Mebarek-Oudina, K. S. Balamurugan, and N. Vedavathi, "Numerical analysis of the magnetic dipole effect on a radiative ferromagnetic liquid flowing over a porous stretched sheet," *Fluid Dynamics & Materials Processing*, vol. 20, no. 2, pp. 293–310, 2024, doi: 10.32604/fdmp.2023.030325.
- [6] B. O. Said, F. Mebarek-Oudina, and M. A. Medebber, "Magneto-hydro-convective nanofluid flow in porous square enclosure," *Frontiers in Heat and Mass Transfer*, vol. 22, no. 5, pp. 1343–1360, 2024, doi: 10.32604/fhmt.2024.054164.
- [7] J. Wang, H. Xie, Z. Guo, L. Cai, and K. Zhang, "Using organic phase-change materials for enhanced energy storage in water heaters: An experimental study," *Journal of Enhanced Heat Transfer*, vol. 26, pp. 167–178, 2019.
- [8] B. O. Said, F. Mebarek-Oudina, and M. A. Medebber, "Magneto-hydro-convective nanofluid flow in porous square enclosure," *Frontiers in Heat and Mass Transfer*, vol. 22, no. 5, pp. 1343–1360, 2024, doi: 10.32604/fhmt.2024.054164.
- [9] M. H. Mousa, N. Miljkovic, and K. Nawaz, "Review of heat transfer enhancement techniques for single phase flows," *Renewable and Sustainable Energy Reviews*, vol. 137, p. 110566, 2021.
- [10] M. Habibishandiz and M. Z. Saghir, "A critical review of heat transfer enhancement methods in the presence of porous media, nanofluids, and microorganisms," *Thermal Science and Engineering Progress*, vol. 30, p. 101267, 2022.
- [11] M. L. G. Ho, C. S. Oon, L. L. Tan, Y. Wang, and Y. M. Hung, "A review on nanofluids coupled with extended surfaces for heat transfer enhancement," *Results in Engineering*, vol. 17, p. 100957, 2023.
- [12] Y. Kuwata, "Reynolds number dependence of turbulent heat transfer over irregular rough surfaces," *Physics of Fluids*, vol. 34, no. 4, 2022.
- [13] S. B. Romdhane, A. Amamou, R. B. Khalifa, N. M. Saïd, Z. Younsi, and A. Jemni, "A review on thermal energy storage using phase change materials in passive building applications," *Journal of Building Engineering*, vol. 32, p. 101563, 2020.
- [14] V. G. Choudhari, A. S. Dhoble, and S. Panchal, "Numerical analysis of different fin structures in phase change material module for battery thermal management system and its optimization," *International Journal of Heat and Mass Transfer*, vol. 163, p. 120434, 2020.
- [15] L. Yang, X. Jin, Y. Zhang, and K. Du, "Recent development on heat transfer and various applications of phase-change materials," *Journal of Cleaner Production*, vol. 287, p. 124432, 2021.